

一份笔记，总算不要预先下载、保存巨量的包来安装牙签了

命令行下编译安装ruijieclient会出现缺少lib的现象，此时需要安装的有以下内容：

代码：

```
sudo pacman -U /path/to/the/packages/libpcap
```

```
sudo pacman -U /path/to/the/packages/zlib(为libxml2)
```

```
sudo pacman -U /path/to/the/packages/readline(为libxml2)
```

```
sudo pacman -U /path/to/the/packages/libxml2
```

```
sudo pacman -U /path/to/the/packages/openssl
```

之后下载ruijieclient的code文件，解压

代码：

```
cd /path/to/the/ruijieclient/package_uncompressed
```

```
sudo ./configure -prefix=/usr
```

```
sudo make
```

```
sudo make install
```

以下的dhcp及dhclient为ruijieclient需要用到的：

代码：

```
sudo pacman -U /path/to/the/packages/dhcp
```

```
sudo pacman -U /path/to/the/packages/dhclient
```

之后：

代码：

```
sudo ruijieclient -g
```

生成配置文件

代码：

```
sudo gedit /etc/ruijie.conf
```

之后，在配置好rc.conf的情况下：

代码：

```
sudo dhcpcd eth0
```

代码：

```
sudo ruijieclient
```

代码：

ping www.google.com

上网。