

```
bear@bear-K40IE:~$ sudo gedit /etc/network/interfaces
[sudo] password for bear:
bear@bear-K40IE:~$ sudo gedit /etc/resolv.conf
bear@bear-K40IE:~$ sudo /etc/init.d/networking restart
 * Running /etc/init.d/networking restart is deprecated because it may not enable again some
interfaces
 * Reconfiguring network interfaces... [ OK ]
bear@bear-K40IE:~$ ping 192.168.16.1
PING 192.168.16.1 (192.168.16.1) 56(84) bytes of data.
64 bytes from 192.168.16.1: icmp_req=1 ttl=255 time=0.560 ms
64 bytes from 192.168.16.1: icmp_req=2 ttl=255 time=0.552 ms
64 bytes from 192.168.16.1: icmp_req=3 ttl=255 time=0.546 ms
64 bytes from 192.168.16.1: icmp_req=4 ttl=255 time=0.554 ms
64 bytes from 192.168.16.1: icmp_req=5 ttl=255 time=0.543 ms
64 bytes from 192.168.16.1: icmp_req=6 ttl=255 time=0.552 ms
64 bytes from 192.168.16.1: icmp_req=7 ttl=255 time=0.553 ms
64 bytes from 192.168.16.1: icmp_req=8 ttl=255 time=0.569 ms
64 bytes from 192.168.16.1: icmp_req=9 ttl=255 time=0.574 ms
64 bytes from 192.168.16.1: icmp_req=10 ttl=255 time=0.555 ms
64 bytes from 192.168.16.1: icmp_req=11 ttl=255 time=0.548 ms
64 bytes from 192.168.16.1: icmp_req=12 ttl=255 time=0.547 ms
```

```
auto lo
iface lo inet loopback
auto eth0
iface eth0 inet static
address 192.168.16.16
netmask 255.255.255.0
network 192.168.16.0
broadcast 192.168.16.255
gateway 192.168.16.1
```

```
nameserver 202.114.112.13
```